

FLEXEM——IIoT HMI FE6000 Series

Model: FE6100CE

Overview

Flexem Industrial HMI 6000 Series, a new generation of IIoT human-machine interface. It is high-quality and cost-effective touch screen, industrial ABS plastic shell, low cost, high reliability. The mainboard is treated with a special coating (three anti-paint) to adapt to harsh environments. The new model opens with a more practical down-line approach, and the redesigned front face has a better looking look, and higher resolution model is available. By selecting the Flink IIoT module, you can upgrade IIoT human-machine interface immediately and uses complete and convenient industrial IIoT cloud platform service.









Appearance




Product specifications

Hardware parameter	Display	10.1" 16:9 TFT LCD
	Resolution (WxH)	1024 × 600
	Colors	24-bit
	Brightness	400 cd/m ²
	Backlight	LED
	LCD Life	50000 hours
	Touch Panel	4 wires resistive touch screen(Surface hardness 4H)
	CPU	600MHz ARM Cortex-A8
	Memory	128M Flash + 128M DDR3
	RTC	Built in
	Ethernet	1 way 10M/100M adaptive
	SD card Port	Available
	USB Port	USB Slave 2.0 port*1,USB Host 2.0 port*1
	Download Project	USB Slave/U disk / Ethernet
	COM Port	COM1/COM3:RS232/RS485/RS422 COM2:RS485
	LCD viewing angle (T/B/L/R)	85'/85'/85'/85'
Electrical Specifications	Power Consumption	< 10W
	Input Power	DC24V, working range DC 9V~28V
	Power Protection	Protected from thunderstrike and surging
	Power Down Allowed	< 5mS
	CE & RoHS	Complied with EN61000-6-2:2005, EN61000-6-4:2007, RoHS, Surge Immunity: ±1KV, EFT: ±2KV,ESD:4KV, Air:8KV
Environmental Specifications	Operating Temperature	0~50C
	Storage Temperature	-20~60C
	Anti-UV	Not suitable to work in strong ultraviolet light (such as direct sunlight)
	Operating Humidity	10~90%RH(non condensate)
	Vibration Endurance	10~25Hz (X,Y,Z direction 2G/30 minutes)
	Cooling	Natural air cooling
Mechanical index	Degree of Protection	Front IP65(with NEMA panel),Back IP20
	Enclosure	ABS+PC
	Panel Cutout	260mm*202mm
	Dimension	273mm*213mm*36mm
	Weight	About 920g


Wiring definition

		
Power terminal (Pin1~Pin3from left to right)		
	Pin1	FG
	Pin2	0V
	Pin3	DC24V
DB9 Serial terminal		
	Pin1	Rx-(B)
	Pin2	RxD (COM1 RS232)
	Pin3	TxD (COM1 RS232)
	Pin4	Tx-
	Pin5	GND
	Pin6	Rx+(A)
	Pin7	RxD (COM3 RS232)
	Pin8	TxD (COM3 RS232)
	Pin9	Tx+
485 terminal (Pin1~Pin2 from left to right)		
	Pin1	A+ (COM2 RS485)
	Pin2	B- (COM2 RS485)
Ethernet port		
	RJ45	Used for Ethernet setup with the controller or for connecting to a server
USB Host		
	USB Type A	Used to connect U disk, scan code gun and other peripherals
USB Slave		
	MicroUSB	Used to download programs and debug
	Expansion module card slot	Support module: FLink, FLink-2G, FLink-4G, FLink-WiFi

Size FE6100CE



Size FE6100CE+FLink



Contact us

Shanghai (R&D Center)

Address: Room 804, Lane 1688, North
Guoquan Road, Yangpu
District, Shanghai, China
Telephone: +86-21-68683993
Fax: +86-21-65107569

Suzhou

Address: Room 915, Ricky Building,
No.668,YutingAvenue,Suzhou
Industrial Park
Telephone: +86-512-69833996

Shenzhen (Factory)

Address: 5th Floor, NO.2 Building,
Lanyun Science Park, Tangtou
Road, Shiyan Town, Baoan
District, Shenzhen, China
Telephone: +86-755-27610682
Fax: +86-755-27629895

Wuxi

Address: Room 1603, Taihu
Mingzhu Development
Building, No. 1890 Taihu
West Road, Binhu
District, Wuxi City
Telephone: +86-18505101982

Beijing

Address: Room 2008, Building 1, No. 93
Jianguo Road, Chaoyang
District, Beijing (Wanda Plaza)
Telephone: +86-10-58204608
Fax: +86-10-58204608

Hangzhou

Address: Room 1005, Building 6,
Dongsha Mingcheng, No.
159, Tiancheng East
Road, Xiasha
Development Zone,
Hangzhou